


# Oil/water alarm unit OM 5

class III, EN 13160-1/-4



- For storage rooms, manholes, drip pans, double-walled tanks
- With visual/audible alarms, Test/Acknowledge buttons and relay output
- Self-monitoring probe

Monitors up to 5 tanks



4

**Application** For visual and audible alarms if liquids with a flash point of  $>55\text{ }^{\circ}\text{C}$  are detected. OM 5 is suitable for the following media: fuel oil, diesel fuel or low-viscosity lubricating oils, motor oils, gearbox oils or hydraulic oils, vegetable oils and transformer oils, water and other liquids. Use as leak detection system class III as per EN 13160-1/-4 and as leak detection system as per TRWS 791-1/-2.

**Description** The unit in a wall mounting housing triggers visual and audible alarms in the event of accumulations of liquids which can be caused by tank leaks, backflow, flooding, etc. OM 5 consists of a control unit with visual/audible alarm, Test and Acknowledge buttons as well as a relay output. Up to five photoelectric probes can be connected. The probes are mounted at the lowest point of the object to be monitored. The alarm is triggered when the probe comes into contact with liquid. The audible alarm can be muted with the Acknowledge button. The visual alarm is cleared once the leak has been removed. The Test button allows you to simulate an alarm condition in order to perform a function check. The voltage-free relay contact is provided for connection of additional alarm equipment (such as additional alarm unit ZAG 01, horn). The alarm units are suitable for panel mounting with a mounting frame. A sealing kit (IP 54) is available for rough application conditions.

**Empty probe** for retrofitting of photoelectric probes in battery tanks

**OM 5/1** with additional probe for detection of minimum or maximum levels, e.g. in fuel oil tanks.

## Technical specifications

### Operating temperature range

Ambient:  $-10/+60\text{ }^{\circ}\text{C}$

### Probe

L x  $\varnothing$ : 33 x 10 mm  
Cable length: 10 m

### Supply voltage

OM 5: AC 230 V or AC/DC 24 V  
OM 5/1: AC 230 V

### Nominal power

5 VA

### Switching output

Relay contact: 1 voltage-free changeover contact

### Alarm sound

Min. 70 dB(A)

### Housing

Wall mounting housing made of impact-resistant plastic (ABS)  
W x H x D: 100 x 188 x 65 mm  
Degree of protection: IP 40 (EN 60529)

### Approval for construction products

DIBt: Z-65.40-214

### Scope of delivery

- OM 5: ■ control unit without probe  
OM 5/1: ■ control unit  
■ 1 photoelectric probe  
■ 1 min./max level probe

i

Please order the photoelectric probes separately

DG: G, PG: 4	Part no.	Price €
<b>Oil/water alarm unit OM 5</b>	<b>44502</b>	
<b>Oil/water alarm unit OM 5, 24 V</b>	44486	
<b>Oil/water alarm unit OM 5/1</b>	<b>44517</b>	
<b>Photoelectric probe 10 m</b>	<b>44503</b>	
<b>Empty probe 1.66 m</b>	43548	