

# Tester for safety equipment against siphoning



Manufacturer-independent application

- Reliable tests of all diaphragm type/piston type anti-siphon valves
- Simple check and assessment of the system safety
- Test can be performed easily at all systems with standard filter combinations



**Application** Tester for function tests of built-in mechanical "safety equipment against siphoning" (diaphragm type or piston type anti-siphon valves) in oil carrying pipes or withdrawal systems. Test can be performed at all systems with standard filter combinations. If no AFRISO filter cup with test and drain system is available, it is sufficient to replace the existing filter cup with the filter cup of the tester. AFRISO recommends to replace all filter cups without drain system so that the fuel oil filter can be drained rapidly and the function test performed easily during servicing. Suitable for tests with the following media: fuel oil EL (DIN 51603-1) and diesel fuel (EN 590) as well as biofuel and biodiesel with up to 100 % FAME.

**Description** The tester for "safety equipment against siphoning" allows to quickly come to a sound conclusion concerning the correct operation of anti-siphon valves. Mounting is simple: Screw the filter cup of the tester into the fuel oil filter of the facility (not necessary in the case of oil filter cups with test and drain system), plug the hose into the tester drain unit, connect an oil suction pump to the other end of the tester and you are ready for testing. For the test, a vacuum is generated which sucks in oil; the oil flows into the tester cup. The vacuum is maintained in the tester cup via the shut-off fitting and displayed by the pressure gauge. When no more oil flows into the tester cup, there is pressure equilibrium. The vacuum can now be read at the test pressure gauge and you can determine whether the siphoning protection works.

## Technical specifications

### Dimensions (W x H x D)

Tester: 180 x 286 x 71 mm  
Case: 395 x 106 x 295 mm

### Range

-0.6/0 bar

### Connection

G $\frac{3}{8}$  with 60° cone

### Operating temperature range

Ambient: -25/+40 °C  
Storage: -25/+60 °C

### Scope of delivery

- Tester with long filter cup
- Vacuum gauge
- Hose
- Long tester cup with drain system
- Plastic case

## i

Safety equipment against siphoning must be checked for correct operation at least every 5 years according to the approval.

See [www.afriso.com](http://www.afriso.com) > INFOTHEK > downloads for test reports.

DG: G, PG: 1			Part no.	Price €
<b>Tester anti-siphon valve</b>	1	-	<b>20239</b>	
Accessories				
<b>Filter cup short</b> with drain system	1	-	<b>20257</b>	
<b>Filter cup long</b> with drain system	1	-	<b>20262</b>	