

## Gas sensor GS 4.1



### Benefits

- Additional sensor suitable for gas alarm unit GS 2.1 and gas alarm unit GM 2.1
- Detectable gases: methane or propane / butane
- LEDs indicate the operating and alarm state of the gas alarm system

### Application

Additional gas sensor to be used with the gas alarm unit GS 2.1. Enables monitoring at two points in different rooms.

### Versions

	Part no.
Gas sensor GS 4.1 Methane	61188
Gas sensor GS 4.1 Propane/butane	61189

Blue part no. = in-stock items

### Description

Remote probe for gas alarm unit GS 2.1. Audible alarm is triggered by the gas alarm GS 2.1.

**Detectable gases:** methane, propane, butane. LEDs at the sensor indicate the operating and alarm state of the gas alarm system:

LED green: operation

LED yellow: error

LED red: gas alarm



## Technical specifications

### Supply voltage

Via GS 2.1

### Housing

Wall mounting plastic housing

W x H x D: 80 x 80 x 36 mm

Weight: Approx. 500 g

Degree of protection: IP 20 (EN 60529)

### Operating temperature range

Ambient: 0/50 °C

Storage: -10/+60 °C

Humidity/moisture: Max. 75 % rH

### Alarm value

Approx. 20 % UEG

### Service life

Approx. 5 Jahre