



2

 **Bluetooth**
SMART

Also
available
as
CAPBs®

LEAK TEST SETS

CAPBs®-enabled set DPK 60-6 ST

- + Ready-to-use test set for professional tightness tests
- + Can be modularly extended for other tests
- + With CAPBs®-enabled digital pressure measuring instrument (S4600 ST) with Bluetooth® Smart technology, high measuring accuracy and barometric pressure determination for compensation of air fluctuations during measurements and for temperature compensation
- + Extended measuring range 0/5,000 bar
- + Integrated timer function for long-term measurements, measuring duration freely selectable in increments of one minute (up to 900 min).
- + Pressure test valve with high-precision adjustment for easy adjustment of the filling pressure
- + microSD card for data management and documentation on the PC
- + Large TFT colour display (W x H: 45 x 60 mm)
- + Convenient quick-action coupling system for easy and fast adaptation to the task at hand
- + Option data logger: Data logging once per second during measurements (XML format)
- + Measurement logs as QR codes



Application For pressure tests as per DVGW worksheet G600. Suitable for tightness tests (150 mbar) and load tests (1 bar) on gas pipes and for checking the connection and flow pressure as well as the pressure loss. Can also be used for tightness tests (150 mbar) and strength tests (3 bar) on drinking water pipes as per ZVSHK (German Central Association of the HVAC Industry). Ideal for acceptance tests of heating system pipes, solar system pipes, underfloor heating systems, liquid gas pipes and oil pipes. The enclosed digital pressure measuring instrument meets the current DVGW (German Technical and Scientific Association for Gas and Water) requirements as per TRGI (German Technical Rules for Gas Installations) and the required reading accuracy (0.1 mbar) for tests of oil pipes.

Technical specifications

Measuring range

± 5,000 mbar

Resolution

0.1 mbar

Operating temperature range

Ambient: 0/40 °C

Storage: -20/+50 °C

Hours of operation

Max. 38 hours

Weight

2.65 kg

Dimensions (W x H x D)

S4600 ST: 66 x 143 x 37 mm

Case: 450 x 136 x 365 mm

Display

TFT colour display, W x H: 45 x 60 mm

Supply voltage

Lithium-ion battery (3.6 V/1,800 mAh)

or USB power supply unit

Scope of delivery

- Digital pressure measuring instrument S4600 ST with Bluetooth® Smart technology, power supply unit and charging cable
- MicroSD card, USB adapter and USB 2.0 card reader
- Pressure test valve with quick-action coupling and high-precision adjustment valve
- Hand-operated bulb pump with valve and connecting hose
- 2 conical test plugs for pipe diameter 3/4" to 1 1/4" with plug-in nipple
- Y connector (2 x quick-action coupling/1 x plug-in nipple)
- Connection hoses with plug-in nipple and quick-action coupling
- System case L "DPK"



See chapter 7 for options and accessories.

DG: H, PG: 4	Part no.	Price €
Leak test set DPK 60-6 ST	560006	