



## CAPBs® set Heating system check sens



### Benefits

- Complete set for performing 4 Pa test in buildings
- Robust, modular system case S, suitable for box and shelf system Sortimo-BOXX
- Wireless, immediate transmission of the measurement data to your AFRISO measuring instrument, smartphone or tablet with Bluetooth® Low energy technology
- Position-independent, temperature-compensated sensor technology for maximum precision in all measuring scenarios
- Free app for EuroSoft live for operation of all CAPBs® via smartphone and tablet. With pre-installed measurement menus for special applications and graphical representation of the measurement results



### Application

Sensor module pressure/temperature CAPBs® sens FP 10 with Pitot tube and surface temperature probe in system case S for measurement of the flow rate and determination of the temperature in the residual core flow of the flue gas line. The measured data is used to calculate the ventilation loss. If the channel cross section is known, it is possible to calculate the volume flow. The measurement results of the surface temperature probe serve as the basis for calculating the surface loss of the heat generator.

### Versions

	DG	PG	Part no.	Price (€)*
CAPBs® set Heating system check sens	H	4	560009	442.00

\* prices plus applicable VAT [Blue part no.](#) = in-stock items



## Technical specifications

### Dimensions (W x H x D)

Sensor module: 42 x 74 x 35 mm  
Case: 260 x 63 x 155 mm

### Weight

0.4 kg

### Measuring range

Pressure: -20/+20 mbar  
Temperature: -50/+600 °C  
Pitot: 0.2/20 m/s

### Accuracy

Pressure:  $\pm 0.003$  mbar (< 0.6 bar)  
Pressure:  $\pm 0.5$  % v. Mw.  $\pm 1$  Digit (> 0.6 mbar)  
Temperature:  $\pm 1.5$  K  
Pitot:  $\pm 0.1$  m/s (< 2 m/s)  
Pitot:  $\pm 5$  % v. Mw. (> 2 m/s)

### Resolution

Pressure: 0.001 mbar  
Temperature: 0.1 °C  
Pitot: 0.1 m/s

### Indication of measured values

hPa, mbar, Pa, mmWs, mmHg, inHg

### Scope of delivery

- System case S