

Boiler safety group assembly KSG Mini



Benefits

- Compact version in form-fit insulation
- Time-saving installation with pre-assembled, tightness-tested assembly
- Quick air vent PrimoVent with two-way venting principle for automatic venting
- Pressure gauge for heating installations for direct indication of the system pressure
- Safety valve for protection against overpressure
- Service-friendly: Pressure gauge and quick air vent can be replaced without draining
- For heating systems with a capacity of up to 50 kW

Versions

	Heat capacity	Response pressure	Boiler connection	Part no.
Boiler safety group assembly KSG Mini	Max. 50 kW	2.5 bar	G1 female	77351
Boiler safety group assembly KSG Mini	Max. 50 kW	3 bar	G1 female	77350

Blue part no. = in-stock items

Technical specifications

Connection boiler
G1 female

Operating temperature range
Max. 120 °C

Dimensions
W x H x D: 147 x 140 x 70 mm

Insulation
Polystyrene EPS

Carrier
Brass

Diaphragm safety valve MS
Inlet x outlet: G¾
Response pressure: 2.5 bar 3 bar

Pressure gauges for heating installations
Range: 0/4 bar
Diameter: 50 mm
Connection: Bottom back

Quick air vents
Input: G¾
Nominal pressure: 12 bar