

## Level indicator MT-Profil R



### Benefits

- No power supply required
- With reversible scale (0–150 cm and 0–250 cm) for fast adaptation to the tank height
- Materials resistant to biofuel and biodiesel with max. 100 % FAME
- Proofed Barrier (odour-tight)
- Watertight up to 10 m water column - ideal for use in flood hazard areas

### Application

For continuous level measurement in tanks containing fuel oil EL, diesel fuel, biodiesel and water. For tanks heights from 0 to 250 cm. Suitable for use in flood hazard areas.

### Versions

	Part no.
Level indicator MT-Profil R connection thread G1½	16500
Level indicator MT-Profil R Connection thread G2	16540
Reducer G2 x G1½	20903
Flange adapter G1½	20900

Blue part no. = in-stock items

### Description

Universal, mechanical level indicator with plastic planetary gear. Measuring range is adjustable from 0 to 250 cm by reversible scale. With reversible scale 0–150 cm and 0–250 cm for fast adaptation to the tank height. Odour-tight. Watertight up to 10 m water column.

### Technical specifications

**Measuring range (tank height)**  
0/150 to 0/250 cm

**Scale (displayed values)**  
0/150 or 0/250 liquid level in cm

**Connection thread**  
G1½ or G2