



LEAK TEST SETS

DPK 60-5

- + Mechanical test set for starters
- + Ideal for pressure tests of gas/oil and water lines
- + 2 pressure gauges for improved reading accuracy
- + Pressure test valve with high-precision adjustment for easy adjustment of the filling pressure
- + Convenient quick-action coupling system for easy and fast adaptation to the task at hand

2

Application For easy tightness checks (150 mbar) and load tests (1 bar) on gas pipes and for checking the connection and flow pressure. Can also be used for tightness checks (150 mbar) and strength tests (3 bar) on drinking water pipes as per ZVSHK (German Central Association of the HVAC Industry). Ideal for acceptance tests of heating system pipes, solar system pipes, underfloor heating systems, liquid gas pipes and waste water pipes. Also suitable for pressure adjustments/tests or vacuum/tightness tests on oil pipes and oil pumps.

Technical specifications

Ranges

Test pressure gauge 1: 0/6 bar
 Test pressure gauge 2: Dual scale 0/200 mbar and 0.5/1.5 bar

Application areas

Atmospheric pressure: 750/1100 hPa
 Humidity: 20/80 % rH

Operating temperature range

Ambient: 0/40 °C
 Medium: 0/40 °C
 Storage: -20/+50 °C

Dimensions

Test pressure gauge with impact protection: Ø 100 mm
 Case (W x H x D): 450 x 136 x 365 mm

Weight

4.6 kg

Scope of delivery

- Pressure gauge 0/6 bar with impact protection
- Pressure gauge with dual scale 0/200 mbar and 0.5/1.5 bar with impact protection
- Pressure test valve with quick-action coupling and high-precision adjustment valve
- Hand-operated bulb pump with valve and connecting hose
- 2 x conical test plug 3/4" to 1 1/4" with plug-in nipple
- 2 x connection hose (300 mm) with quick-action coupling and plug-in nipple
- Connection hose (1 m) with quick-action coupling and plug-in nipple
- Y connector with shut-off valve, 2 x quick-action coupling and 1 x plug-in nipple
- Robust plastic case with foam inlay



DG: H, PG: 4	Part no.	Price €
Leak test set DPK 60-5	569290	